



THERMOLAMINATED vinyl door & panel care

Your **THERMOLAMINATED** vinyl doors and panels are manufactured from the highest quality materials and designed to provide years of trouble free service.

Whilst your doors are made from a Moisture Resistant Medium Density Fibreboard (MR MDF) and as with any wood based panel cannot be made totally waterproof, care should be taken to wipe up spills immediately, ensuring the doors are not exposed to high or continuous levels of moisture, steam and humidity.

THERMOLAMINATED vinyl doors and panels should be cleaned as follows:

Stains

Wipe down using a damp soft cloth containing warm soapy water.

For more stubborn stains use a mild household cleaning spray as per the manufacturers recommendation.

Always ensure that you refer to the recommendations provided by the cleaning product manufacturer before use.

To ensure that your **polytec** Guarantee will not be void, **DO NOT** use any of the following on **THERMOLAMINATED** vinyl doors and panels:

Commercial Cleaning Products, Abrasive Cleaners, Scouring Pads or Abrasive Papers, Acids and Alkalis, Solvents, Thinners, Turpentine (Turps), Ammonia, Bleach, Methylated Spirits, Acetone, M.E.K. and any other cleaning agents containing Organic Solvents or the above mentioned products.

Please note: polytec provide a limited seven (7) year warranty on all door products which insures against design, workmanship & manufacturing defects. If you detect any problems with your doors polytec must be notified within seven (7) years from the date your doors were manufactured. Failure to follow the above care instructions could result in damage to your door and void your entitlement to the warranty.